

GREEN PROTECTION FILM

TECHNICAL DATA SHEET **4007**

V1.12/21

PRODUCT DESCRIPTION

Green Protection Film is a reliable and versatile, low-tack general-purpose product for the protection of surfaces. Green Protection Film offers a cost-effective solution for general purpose use requiring a film where moderate temperature resistance, light surface protection and easy, clean removal is required. Can be supplied in a variety of widths. See 4008 for the Blue version of this product.

PRODUCT CONSTRUCTION



SHELF LIFE

One year from date of receipt by customer when stored at 25°C ±10°C (77°F ±18°F) and 60% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

| | |
|-----------|--|
| Carrier | PE Film |
| Adhesive | Acrylic-based |
| Colour | Green (Translucent) |
| Thickness | 50µm / 0.05mm (±10%) |
| Width | Various options: 35mm, 50mm, 100mm, 150mm, 400mm (±5%). Other widths available on request. |
| Length | 250m 500m (Other lengths available on request) |

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

| | |
|------------------------|-----------------------------|
| Peel Adhesion | 0.5N/cm (±0.15) |
| Elongation at Break | >200% |
| Temperature Resistance | 70°C/158°F (up to 24 hours) |

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.